



Industrial Hose Products



39496-000
July 30, 2009
Supersedes 39496-000
July 30, 2007

Petroleum Transfer Hose

Blacksnake® (Curb Pump - Hardwall)

(Specification 3624)

| Nom. I.D. | ⊖ | Nom. O.D. | ⊖ | Max. W.P. | ⊖ | Suction | | Min. Bend Radius | ⊖ | Wt. Per Ft. | ⊖ | Standard Pack | Stock (X) or Minimum Order Qty. | Gates Item No. |
|--------------|------|--------------|------|--------------|-------|----------|---------|---------------------|------|----------------|------|------------------|---------------------------------------|-------------------|
| (In.) | (mm) | (In.) | (mm) | (psi) | (MPa) | (In. Hg) | (mm Hg) | (In.) | (mm) | (Lbs.) | (Kg) | | | |
| 5/8 | 15.9 | 1.00 | 25.4 | 150 | 1.03 | 30.0 | 762 | 6.0 | 152 | .37 | .17 | Reel | X | 3624-0001 |
| 3/4 | 19.1 | 1.13 | 28.7 | 150 | 1.03 | 30.0 | 762 | 6.0 | 152 | .42 | .19 | Reel | X | 3624-0002 |
| 1 | 25.4 | 1.38 | 35.1 | 150 | 1.03 | 30.0 | 762 | 8.0 | 203 | .57 | .26 | Reel | X | 3624-0003 |

RECOMMENDED FOR: Dispensing all types of commercial gasolines, or other petroleum based products, from service station pumps. A heavy duty hardwall hose which does not collapse in reel use or behind the nozzle in heavy duty service.

TEMPERATURE: -40°F to +120°F (-40°C to +49°C) continuous service.

CONSTRUCTION: **Tube:** Type C (Nitrile). Black.
Reinforcement: Braided, high tensile steel wire.
Cover: Type J (CPE). Black.

COUPLINGS: 24. Reference the Hose Coupling Section.

PACKAGING: 5/8" through 1": Packaged 500' per reel. Maximum 5 pieces. Minimum length 12'.

BRANDING: Continuous transfer label. Example: "GATES® BLACKSNAKE® 3/4 Inch (19.1mm) 1 wire braid (UL) Listed Gasoline Hose Made In U.S.A."

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 5,000 feet per size.

REMNANT LENGTHS: None.

STANDARDS: Underwriters Laboratories Standard No. 330. (USA and Canada).
Tube: RMA (Class A) High oil resistance.

Due to continual product improvements, Gates reserves the right to alter specs and prices without prior notice.

