

High Pressure

Global G2 2-Wire Braid Hose— SAE 100R2 Type AT

(Meets Flame Resistance Acceptance Designation "MSHA 2G")

Recommended For: High-pressure hydraulic oil lines. Meets or exceeds the requirements of SAE 100R2AT and SAE 100R2 Type S and performance requirements of EN 853 2SN. Qualified to Mil-DTL-13531 Type II Class B.

Tube: Black, oil resistant, synthetic rubber (Nitrile - Type C). See Hose Stock Characteristics.

Reinforcement: Two braids of high-tensile steel wire.

Cover: Black, oil and abrasion resistant, thin synthetic rubber (Modified Nitrile - Type C2). See Hose Stock Characteristics.

Temperature Range: -40°F to +212°F (-40°C to +100°C). For water emulsions see Temperature Limits Table.

Coupling Recommendation (See Crimp Data Manual 35019):

Field Attachable 'Type T' Couplings

MegaCrimp® Couplings (except -24 and -32)

Permanent GSP Couplings (-24 and -32)



Description	Product No.						Packaging	Standard Pack
3G2XREEL	4657-2182	3/16	0.52	6,000	24,000	3.5	E	440
4G2XBALE	4657-5708	1/4	0.58	5,800	23,200	4.0	R	5600
4G2XREEL	4657-0125	1/4	0.58	5,800	23,200	4.0	E	550
6G2 XREEL	4657-0126	3/8	0.73	4,800	19,200	5.0	E	400
6G2XBALE	4657-5709	3/8	0.73	4,800	19,200	5.0	R	3000
8G2 XREEL	4657-0127	1/2	0.86	4,000	16,000	7.0	F	330
8G2XBALE	4657-5710	1/2	0.86	4,000	16,000	7.0	R	2250
10G2XBALE	4657-5711	5/8	0.98	3,625	14,500	8.0	R	1800
10G2XREEL	4657-0132	5/8	0.98	3,625	14,500	8.0	F	220
12G2XBALE	4657-5712	3/4	1.14	3,100	12,400	9.5	R	1250
12G2XREEL	4657-0128	3/4	1.14	3,100	12,400	9.5	F	220
16G2XBALE	4657-1094	1	1.48	2,400	9,600	12.0	R	1000
16G2XREEL	4657-0129	1	1.48	2,400	9,600	12.0	F	165
20G2XCTN	4657-0644	1 1/4	1.87	1,825	7,300	16.5	A	120
24G2XCTN	4657-2491	1 1/2	2.15	1,300	5,000	20.0	A	120
32G2XCTN	4657-2492	2	2.65	1,175	4,500	25.0	A	120



The World's Most Trusted Name in Belts, Hose and Hydraulics.

www.gates.com/hydraulics

A29