



Recommended For: Hydraulic oil lines, anti-freeze solutions or water. Meets or exceeds requirements of SAE 100R3.

Tube: Black, synthetic rubber (Nitrile - Type C). See Hose Stock Characteristics.

Reinforcement: Two fiber braids.

Cover: Black, oil and abrasion resistant, synthetic rubber (Neoprene - Type A). See Hose Stock Characteristics.

Temperature Range: For hydraulic oil lines -40°F to +275°F (-40°C to +135°C) constant and +300°F (+149°C) intermittent (up to 10% of operating time). For water emulsions see Temperature Limits Table.

Coupling Recommendation (See Crimp Data Manual 35019):

Permanent Power Crimp® Couplings



Description	Product No.							Packaging	Standard Pack
4G3HXCTN	3319-0088	1/4	0.56	1,250	5,000	3.0	28	D	455
5G3HXCTN	3319-4287	5/16	0.66	1,200	4,750	3.5	28	D	330
6G3HXCTN	3319-0087	3/8	0.75	1,125	4,500	4.0	28	D	350
8G3HXCTN	3319-0090	1/2	0.94	1,000	4,000	5.0	28	D	225
10G3HXCTN	3319-4288	5/8	1.10	900	3,500	5.5	28	D	200
12G3HXCTN	3319-0091	3/4	1.25	750	3,000	6.0	28	D	160
16G3HXCTN	3319-0092	1	1.50	565	2,250	8.0	20	M	120
20G3HXCTN	3319-0071	1 1/4	1.75	375	1,500	10.0	15	D	120
24G3HXCTN	3319-4289	1 1/2	1.94	300	1,200	12.0	10	D	120



The World's Most Trusted Name in Belts, Hose and Hydraulics.

www.gates.com/hydraulics

A39

