



Steam Hoses

PreMluM™ Heater Master



								
mm	mm	mm	Bar	Bar	Bar	Kg/m	m	REF.
13	25	6	6	20	60	0.5	40	3213-11001
16	30	7	6	20	60	0.6	40	3213-11002
19	33	7	6	20	60	0.8	40	3213-11003
25	40	7.5	6	20	60	0.9	40	3213-11004
32	48	8	6	20	60	1.2	40	3213-11005
38	54	8	6	20	60	1.4	40	3213-11006
51	67	8	6	20	60	1.8	40	3213-11007

RECOMMENDED FOR

Premium hot water (20 bar up to 90°C) delivery and steam hose up to 164°C, 6 bar working pressure in general industrial applications.

TUBE

Black ePDM, smooth

REINFORCEMENT

High tensile textile cord

COVER

ePDM rubber, smooth, black. extremely weather resistance cover

TEMPERATURE

-20 °C to +164°C

BURST PRESSURE

60 Bar

ELECTRICALLY CONDUCTIVE

$r < 10^6$ ohm

STANDARDS

exceeds BS 5122/A2

BRANDING TRANSFER LABEL

PreMluM™ HeATER MASTER - STeAM oPen SYSTeM 6 BAR 164°C Ω

