

High Pressure

## J2AT 2-Wire Braid Jack Hose— 10,000 Static Pressure Only



(Meets Flame Resistance Acceptance Designation "MSHA 2G")

**Recommended For:** Hydraulic jack applications. Meets Material Handling Institute specification IJ 100 for hydraulic hose and assemblies used with jacking systems. 10,000 Static Pressure Only  
**Tube:** Black, oil resistant, synthetic rubber (Nitrile - Type C). See Hose Stock Characteristics.

**Reinforcement:** Two braids of high-tensile steel wire.






**Cover:** Black, oil and abrasion resistant, synthetic rubber (Modified Nitrile - Type C2). Available with unique abrasion-resistant MegaTuff® cover. See Hose Stock Characteristics.

**Temperature Range:** -40°F to +120°F (-40°C to +49°C).

**Coupling Recommendation (See Crimp Data Manual 35019):**

Use MegaCrimp® Male Pipe Long Nose Couplings on jack end of assembly for engagement.



Description	Product No.						Packaging	Standard Pack
4J2ATXREEL	4657-1400	1/4	0.58	10,000	20,000	4.0	F	350
6J2ATXREEL	4657-1404	3/8	0.74	10,000	20,000	5.0	F	330



The World's Most Trusted Name in Belts, Hose and Hydraulics.

[www.gates.com/hydraulics](http://www.gates.com/hydraulics)

A31

