



Industrial Hose Products/List Prices



39496-000
July 1, 2006
Supersedes 39496-000
January 17, 2005

Air and Multi-Purpose Hose

LOL Plus (Lock-On Hose)

(Specification 3284D, E, G, H, R, Y)

	Nom. I.D.		Nom. O.D.		Max. W.P.		Suction		Min. Bend Radius		Wt. Per Ft.		Standard	Stock (X) or Minimum	Gates	List Price
Color	(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)	Pack	Order Qty.	Item No.	Per Ft.
Black	1/4	6.4	.47	11.9	300	2.07	27.9	711	3.0	76	.09	.04	REEL	X	3201-1100	\$1.56
Black	3/8	9.5	.63	15.9	300	2.07	27.9	711	3.0	76	.11	.05	REEL	X	3201-1101	1.96
Black	1/2	12.7	.77	19.6	300	2.07	27.9	711	5.0	127	.15	.07	REEL	X	3201-1102	2.29
Black	5/8	15.9	.94	23.9	300	2.07	27.9	711	6.0	152	.20	.09	REEL	X	3201-1103	3.05
Black	3/4	19.1	1.06	26.9	300	2.07	15.0	381	7.0	178	.24	.11	REEL	X	3201-1104	3.81
Blue	1/4	6.4	.47	11.9	300	2.07	27.9	711	3.0	76	.09	.04	REEL	X	3201-1105	1.56
Blue	3/8	9.5	.63	15.9	300	2.07	27.9	711	3.0	76	.11	.05	REEL	X	3201-1106	1.96
Blue	1/2	12.7	.77	19.6	300	2.07	27.9	711	5.0	127	.15	.07	REEL	X	3201-1107	2.29
Blue	5/8	15.9	.94	23.9	300	2.07	27.9	711	6.0	152	.20	.09	REEL	X	3201-1108	3.05
Blue	3/4	19.1	1.06	26.9	300	2.07	15.0	381	7.0	178	.24	.11	REEL	X	3201-1109	3.81
Red	1/4	6.4	.47	11.9	300	2.07	27.9	711	3.0	76	.09	.04	REEL	X	3201-1110	1.56
Red	3/8	9.5	.63	15.9	300	2.07	27.9	711	3.0	76	.11	.05	REEL	X	3201-1111	1.96
Red	1/2	12.7	.77	19.6	300	2.07	27.9	711	5.0	127	.15	.07	REEL	X	3201-1112	2.29
Red	5/8	15.9	.94	23.9	300	2.07	27.9	711	6.0	152	.20	.09	REEL	X	3201-1113	3.05
Red	3/4	19.1	1.06	26.9	300	2.07	15.0	381	7.0	178	.24	.11	REEL	X	3201-1114	3.81
Yellow	1/4	6.4	.47	11.9	300	2.07	27.9	711	3.0	76	.09	.04	REEL	X	3201-1115	1.56
Yellow	3/8	9.5	.63	15.9	300	2.07	27.9	711	3.0	76	.11	.05	REEL	X	3201-1116	1.96
Yellow	1/2	12.7	.77	19.6	300	2.07	27.9	711	5.0	127	.15	.07	REEL	X	3201-1117	2.29
Yellow	5/8	15.9	.94	23.9	300	2.07	27.9	711	6.0	152	.20	.09	REEL	X	3201-1118	3.05
Yellow	3/4	19.1	1.06	26.9	300	2.07	15.0	381	7.0	178	.24	.11	REEL	X	3201-1119	3.81
Green	1/4	6.4	.47	11.9	300	2.07	27.9	711	3.0	76	.09	.04	REEL	X	3201-1120	1.56
Green	3/8	9.5	.63	15.9	300	2.07	27.9	711	3.0	76	.11	.05	REEL	X	3201-1121	1.96
Green	1/2	12.7	.77	19.6	300	2.07	27.9	711	5.0	127	.15	.07	REEL	X	3201-1122	2.29
Green	5/8	15.9	.94	23.9	300	2.07	27.9	711	6.0	152	.20	.09	REEL	X	3201-1123	3.05
Green	3/4	19.1	1.06	26.9	300	2.07	15.0	381	7.0	178	.24	.11	REEL	X	3201-1124	3.81
Gray	1/4	6.4	.47	11.9	300	2.07	27.9	711	3.0	76	.09	.04	REEL	X	3201-1125	1.56
Gray	3/8	9.5	.63	15.9	300	2.07	27.9	711	3.0	76	.11	.05	REEL	X	3201-1126	1.96
Gray	1/2	12.7	.77	19.6	300	2.07	27.9	711	5.0	127	.15	.07	REEL	X	3201-1127	2.29
Gray	5/8	15.9	.94	23.9	300	2.07	27.9	711	6.0	152	.20	.09	REEL	X	3201-1128	3.05
Gray	3/4	19.1	1.06	26.9	300	2.07	15.0	381	7.0	178	.24	.11	REEL	X	3201-1129	3.81

RECOMMENDED FOR: Petroleum-base hydraulic oils, water, glycol antifreeze solutions, hot lubricating oils, and air.

NOTE: Lock-On hose and couplings are not recommended for pressure surge applications or critical applications, such as permanent piping in residential or commercial buildings.
Not recommended for gasoline or diesel fuels.

TEMPERATURE: -40°F to +212°F (-40°C to +100°C) normal service. For temperatures exceeding 160°F use hose clamps.

CONSTRUCTION: **Tube:** Type C (Nitrile). Black.
Reinforcement: Braided, high tensile synthetic textile cord.
Cover: Type A (Neoprene). Black.
Type C₂ (Modified Nitrile). Blue, Red, Yellow, Green or Gray.

COUPLINGS: Gates Hydraulic Lock-On Couplings (Reference Gates Hydraulic Hose Catalog #35093).

PACKAGING: 1/4" through 1/2": Packaged in 300' reels. Maximum of 3 pieces per reel. Minimum length 50 ft.
5/8": Packaged in 250' reels. Maximum of 3 pieces per reel. Minimum length 50 ft.
3/4": Packaged in 225' reels. Maximum of 3 pieces per reel. Minimum length 50 ft.

BRANDING: Continuous ink brand. Example: " LOL PLUS 12LOLA+ 3/4 INCH 300 PSI WP FLAME RESISTANT COVER MADE IN U.S.A."

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 5,000 feet per size.

REMNERANT LENGTHS: None.

STANDARDS: **Tube:** RMA (Class A) High oil resistance.
Cover: RMA (Class A) High oil resistance. Flame-resistant.

Due to continual product improvements, Gates reserves the right to alter specs and prices without prior notice.

