



## M2T® MegaFlex® 2-Wire Braid Hose—SAE 100R16 High Pressure

(Meets Flame Resistance Acceptance Designation "MSHA 2G")

**Recommended For:** High-pressure hydraulic oil lines. Exceeds SAE 100R16. M2T hose has smaller exterior dimensions and significantly tighter bend radius.

**Tube:** Black, oil resistant, synthetic rubber (Nitrile - Type C). See Hose Stock Characteristics.

**Reinforcement:** Two braids of high-tensile steel wire.

**Cover:** Black, oil, abrasion and weather resistant, synthetic rubber (Modified Nitrile - Type C2). Dual green stripe layline. Available with unique abrasion-resistant MegaTuff® cover. See Hose Stock Characteristics.

**Temperature Range:** -40°F to +212°F (-40°C to +100°C). For water emulsions see Temperature Limits Table.

**Coupling Recommendation (See Crimp Data Manual 35019):**  
MegaCrimp® Couplings  
Permanent Stainless Steel Power Crimp® Couplings



| Description   | Product No. |  |  |  |  |  | Packaging | Standard Pack |
|---------------|-------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-----------|---------------|
| 4M2TXBALE     | 4657-5728   | 1/4                                                                               | 0.54                                                                              | 5,000                                                                             | 20,000                                                                            | 2.0                                                                                | R         | 5600          |
| 4M2TXREEL     | 4657-1552   | 1/4                                                                               | 0.54                                                                              | 5,000                                                                             | 20,000                                                                            | 2.0                                                                                | E         | 550           |
| 6M2TXBALE     | 4657-5729   | 3/8                                                                               | 0.69                                                                              | 4,000                                                                             | 16,000                                                                            | 2.5                                                                                | R         | 3000          |
| 6M2TXLRG REEL | 4657-1492   | 3/8                                                                               | 0.69                                                                              | 4,000                                                                             | 16,000                                                                            | 2.5                                                                                | D         | 1700          |
| 6M2TXREEL     | 4657-1555   | 3/8                                                                               | 0.69                                                                              | 4,000                                                                             | 16,000                                                                            | 2.5                                                                                | E         | 385           |
| 8M2TXBALE     | 4657-5730   | 1/2                                                                               | 0.81                                                                              | 3,500                                                                             | 14,000                                                                            | 3.5                                                                                | R         | 2500          |
| 8M2TXLRG REEL | 4657-1493   | 1/2                                                                               | 0.81                                                                              | 3,500                                                                             | 14,000                                                                            | 3.5                                                                                | D         | 1250          |
| 8M2TXREEL     | 4657-1559   | 1/2                                                                               | 0.81                                                                              | 3,500                                                                             | 14,000                                                                            | 3.5                                                                                | F         | 330           |
| 10M2TXBALE    | 4657-5577   | 5/8                                                                               | 0.95                                                                              | 3,000                                                                             | 12,000                                                                            | 4.0                                                                                | R         | 1750          |
| 10M2TXREEL    | 4657-1563   | 5/8                                                                               | 0.95                                                                              | 3,000                                                                             | 12,000                                                                            | 4.0                                                                                | F         | 220           |
| 12M2TXBALE    | 4657-5732   | 3/4                                                                               | 1.10                                                                              | 2,250                                                                             | 9,000                                                                             | 4.8                                                                                | R         | 1500          |
| 12M2TXREEL    | 4657-1567   | 3/4                                                                               | 1.10                                                                              | 2,250                                                                             | 9,000                                                                             | 4.8                                                                                | F         | 220           |
| 16M2TXREEL    | 4657-1571   | 1                                                                                 | 1.38                                                                              | 2,000                                                                             | 8,000                                                                             | 6.0                                                                                | F         | 165           |