

## essential™ oil Master Lite sd



mm	mm	mm	Bar	Bar	mm	Kg/m	m	REF.
19	29	5	10	30	95	0.5	40	4688-14101
25	35	5	10	30	125	0.6	40	4688-14102
32	42	5	10	30	160	0.9	40	4688-14103
38	48	5	10	30	190	1.0	40	4688-14104
51	61	5	10	30	255	1.4	40	4688-14105
65	77	6	10	30	325	2.3	40	4688-14106
76	88	6	10	30	380	2.7	40	4688-14107
90	104	7	10	30	450	3.5	40	4688-14108
100	114	7	10	30	500	3.9	40	4688-14109
127	143	8	10	30	635	6.1	40	4688-14110
152	168	8	10	30	760	7.9	40	4688-14111

\*\* Vacuum resistance up to -0.9 bar

### RECOMMENDED FOR

Very flexible corrugated vacuum and pressure hose (SD) for transfer of fuel oil and other petroleum based products in home delivery, commercial and industrial service or in low pressure return lines. Transfer of refined fuels (commercial gasoline and diesel fuel), oils and other petroleum products. Ideal for oilfield service truck use. Service life of transfer hoses can be extended by draining hoses after use. Max 50% aromatic content.

### TUBE

Black nBr rubber, smooth and oil resistant

### REINFORCEMENT

High tensile synthetic textile cord, steel wire helix and two crossing anti-static wires.

### COVER

Cr rubber, black, corrugated with cloth impression, good resistant to weather and abrasion, chemical and oil resistance.

### TEMPERATURE

-30°C to 100°C

### BURST PRESSURE

> 30 bar

### ELECTRICALLY CONDUCTIVE

$r < 10^6$  ohm

### BRANDING TRANSFER LABEL

eSSenTIAI™ oil MASTER ITe Sd - 10 BAR Ω

